## State of California AIR RESOURCES BOARD

## **EXECUTIVE ORDER A-3-204-2** Relating to Certification of New Motor Vehicles

## DAIMLERCHRYSLER AG

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below:

Model Year: 2001

Vehicle Type: Passenger Car

Exhaust Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type: Gasoline

Test Group: 1MBXV03.2LTR

Engine Displacement: 3.2 Liters

Evaporative Family (Evap): 1: 1MBXR0155MNA

## Special Features and Exhaust Emission Control Systems:

Sequential Multiport Fuel Injection Dual Warm Up Three Way Catalytic Converters Dual Three Way Catalytic Converters Dual Heated Oxygen Sensors (two) Secondary Air Injection Exhaust Gas Recirculation

Models Covered:

Evap 1: Mercedes-Benz SLK 320

Evap 2: Mercedes-Benz CLK 320, CLK 320 (Cabriolet)

The exhaust certification emission levels and standards, in grams per mile, of nonmethane organic gases (NMOG), carbon monoxide (CO), oxides of nitrogen (NOx), and formaldehyde (HCHO) for the listed vehicle models are as follows. The NMOG exhaust certification emission levels include application of the reactivity adjustment factor (RAF) as specified.

The evaporative hydrocarbon (HC) certification emission levels and standards for three-day diurnal plus hot soak (3D) and two-day diurnal plus hot soak (2D) in grams per mile, and onboard refueling vapor recovery follows.

Type of		, ocu, ,	or the listed v	obling vapor re
Emission	ns <u>Mile</u>	) e	-α γι	ehicle models a
<u>EXHAUST</u> @ N ····· NMOG fle NMOG	MOG RAF = 0.94 et average	<u>Ce</u>	rtification Level	<u>Certification</u> Standards
NMOG CO CO NOx NOx NOx (highway NOx (highway HCHO HCHO HCHO CO (20°F) NMOG (50°F) CO (50°F) NOx (50°F) HCHO (50°F)	100,000 50,000 100,000 50,000 50,000 4,000	0.062 (p 0.020 0.028 0.2 0.4 0.1 0.01 0.02 0.0002 0.0002 1.1 0.037 0.3	0.0 0.0 0.0 0.0 10.0	4 015 018
EVAPORATIVE HC-2D HC-3D HC-BI	100.000 <u>Eva</u>	0.1 0.0002 <u>p 1 Evap 2</u>	0.18 3.4 0.2 0.030	)
HC-ORVR  BE IT FURTHER RESOLVE average compliance plan sh Emission Standards and The	100,000 0.2	0.7	Evap 1 8 2.5 2.0 0.05 0.20	2

BE IT FURTHER RESOLVED: That any debit in the manufacturer's NMOG fleet average compliance plan shall be equalized as required by the "California Exhaust Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles"

BE IT FURTHER RESOLVED: (For all listed vehicle models produced on and before July 31, 2000) That the manufacturer is certifying those vehicle models on and before pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) Year Passenger Cars, Light-Duty Trucks and Model.

BE IT FURTHER RESOLVED: (For all listed vehicle models produced on and after August 1, 2000) That those vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1).

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with the following California emission regulations and requirements. Vehicles certified under this Executive Order shall conform to all applicable California emission regulations and requirements.

- Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks (Title 13, California Code of Regulations, Section 2235)
- Motor Vehicle Emission Control and Smog Index Label Specifications (Title 13, California Code of Regulations, Section 1965)
- Emission Control System Warranty (Title 13, California Code of Regulations, Sections 2035 et seq.)
- High-Altitude Requirements and California Inspection and Maintenance Emission Standards (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles)

The Bureau of Automotive Repair will be notified by copy of this order.

Executive Order A-3-204-1 dated July 10, 2000, is superseded and replaced by Executive Order A-3-204-2.

Executed at El Monte, California this 17 day of July 2000.

R. B. Summerfield, Chief

Mobile Source Operations Division

huma hild